Dimensions (Unit: mm)

Bench type (B)



Pole type (P)



Elevated type (EV)



Hanging type (H)



Standard specification

Model			UNI-8
Variation*1			Bench, Pole, Eleveted, Hanging, RP
Scale Unit	Capacity x Division		0-6kg x 0.002kg / 6-15kg x 0.005kg (Multi-interval) 0-15lb x 0.005lb / 15-30lb x 0.01lb (Multi-interval)
			0-15kg x 0.005kg (Single range) 0-30lb x 0.01lb (Single range)
	Scale platter size		Bench / Pole / Eleveted: 310 x 286mm Hanging: ø382mm RP: 390 x 270mm
Display	Size of operator side		10.1"
	Size of customer side		7"
	System		Capactive touch panel
Printer	Media type		Die-cut label / Continuous label / Linerless Label (Manual/Auto cut) / Receipt
	Media size	Outside diameter of roll	Max. 100mm (3.93") or less
		Inner core diameter	40mm +/- 1mm (1.5")
		Width	30-64mm (Linerless label: 60mm)
		Length	30-200mm (Linerless label: 30-175mm)
	Cassette		Non-cassette (Virtual cassette function)
	Thermal head		2"
	Resolution		8dot/mm (200dpi)
	Speed of printing (MAX)		120mm/sec
	Printing width (MAX)		56mm
	Printing length (MAX)		200mm
	Barcode type		JAN, EAN, EAN128, CODE128, UPC, ITF, GS1, QR, DATA MATRIX
Control	I/O port		TCP/IP, USB, RS-485, Connector for external scale
	OS		Linux
	Communication		Wireless

*1) Self Service mode is available for any variation.

The information in this catalog is current as of February 3, 2023.
The company name and product name described in this catalog are registered trademarks.
The machine color in this catalog might be differ from the real machine.
The described machine appearance and specifications in this catalog are subject to change without any notification.

ABLE SCALES QLD
SALES | SERVICE | HIRE
(07) 3208 8382
ablescales.com.au

Printed in Japan 0223(SK) No.6311

ISHIDA

Price Computing Scale Printer

UNI-8

Weighing | Packing | Inspection | Display | Sell

Outstanding Usability and High-Speed Communication

Counter-Top Scale for More Attractive Sales Floor

UNI-8

Flexibility

The 10-inch LCD operation screen can be freely customized in any layout and the scale type can be selected from a wide variety of models.
Smooth service is achievable with UNI-8's flexibility to match the customer's operation and store / sales formats.

Capability

Processing speed is improved from the conventional models to support busy operations at the stores.
Many videos and pictures can be managed in the scale thanks to larger memory capacity, contributing to more appealing promotion on the customer side display.

Connectivity

High-speed data communication is realized on this PC-based scale.
Video downloading and connection with the state-of-the-art technologies such as remote maintenance are enabled.
The platform with the ability to speedily connect with various systems supports the sales over the counter.

10-inch LCD for an Easily Viewable and Freely Customizable Layout

The desired layout for variable users is now achievable with having a 10 inch LCD and more flexibility in design for operation screen.

Support of Multiple Label Types

Various types of media are available to use such as liner labels, linerless labels or receipt papers.
Easy and quick replacement are enabled by the side-loading setting method, which reduces the downtime during the busy operations at stores.

Fascinated Color Display

Thanks to a capability to show the stunning images and videos on the customer or the operator side display, more promotions or cross-selling are available. Displaying operation methods can also contribute to error-free work and help training for new employees.

High-speed Data Communication

The high speed commnication speed makes it possible to receive and work with large files without any inconvenience.
The platform with state-of-the-art technologies would have more compatibility and flexibility with external systems.

* Based on internal survey in 2021.

The high speed reseponse

▸▸▸ Gigabit Ethernet

Variation Lineup

The best suited model is selectable for your style.

Bench type (B)

Pole type (P)

Elevated type (EV)

Hanging type (H)